

### DATA SHEET - SERVICE MANUAL

## APPLICATION

Directional spool valves type **WE6...**, electrically operated, are used to control the direction of fluid flow in the system and thus allows the receiver (mostly piston rod or hydraulic motor) to change direction of movement and also to use two functions *on* and *off*. They are intended for subplate mounting in any position in hydraulic systems.


Directional spool valve is complied with the regulations of directive **2006/95/WE** for the following voltages:

- 50 – 250 V for AC
- 75 – 250 V for DC



## DESCRIPTION OF OPERATION

4WE 6J -12/G42NZ4




Main elements of directional spool valve type **WE6...** are: housing (1), solenoids (3), control spool (2), centering springs (4) and manual overrides (5).

The spool (2) is shifted when it is moved into one of end positions by the force of solenoid (3) affecting it. The return of the spool into neutral position and centering are secured by the centering springs (4). The shape of the spool (control edge spacing) affects the configuration of connections among the ports: **A**, **B**, **P** and **T**.


In case of emergency, the spool can be shifted manually by means of the override (5) – only for version with manual override.

When the situation is anticipated, directional spool valve must be mounted in the way as to be available.




**WE6...-12/OF...** - only for spools: **A**, **C**, **D**. Two-position directional spool valve without return springs with detent. The spool (2) is positioned and supported with detent (6), and its shift results from supplying voltage to one solenoid (3).

## DESCRIPTION OF OPERATION



WE6...-12/O...- only for spools: **A, C, D**. Two-position directional spool valve without return springs. The spool is positioned and supported with attached solenoid. There is no neutral position as the spool is not positioned.





WE6...-12/...**B**... - directional spool valve designation like that, has throttle insert in port **P**.

## TECHNICAL DATA


Hydraulic fluid	mineral oil			
<b>Required filtration</b>	<b>up to 16 μm</b>			
Recommended filtration	up to 10 μm			
Nominal fluid viscosity	37 mm <sup>2</sup> /s at temperature 55 °C			
Viscosity range	2,8 up to 380 mm <sup>2</sup> /s			
Fluid temperature range (in a tank)	recommended	40 °C up to 55 °C		
	max	-20 °C up to +70 °C		
Ambient temperature range	- 20 °C up to +50 °C			
<b>Maximum operating pressure</b>	<b>ports P, A, B</b>	<b>31, 5 MPa</b>		
	<b>port T</b>	<b>21 MPa</b>		
Flow section in central position schemes on page 3	spool	<b>Q</b>		<b>W</b>
	flow section	6 % nominal flow		3 % nominal flow
Switching time	ON	up to 60 ms		
	OFF	up to 40 ms		
Maximum switching frequency	15000 on/h			
Weight	with 1 solenoid	max 1,5 kg		
	with 2 solenoids	max 2,1 kg		
<b>Supply voltage for solenoids</b>	<b>DC</b>			<b>AC (plug-in connector with rectifier)</b>
	<b>12V</b>	<b>24V</b>	<b>110V</b>	<b>230V - 50Hz</b> <b>110V - 50Hz</b>
Supply voltage tolerances	±10%			
Power requirement (DC)	<b>30 W</b>			
<b>Insulation</b>	<b>IP 65</b>			
Solenoid coil temperature	max 150 °C			

## ASSEMBLY AND APPLICATION REQUIREMENTS



1. Only valve working properly and suitably installed may be connected to an electric system. Only skilled workers are allowed to connect and disconnect electric system.
2. Ground connection (  ) must be connected with protective earth wire ( PE  ) in supply system according to instructions.
3. It is forbidden to use directional spool valve when tightness and appropriate clamp for cable in the plug gland is not secured.
4. It is forbidden to use directional spool valve when the plug is not precisely tightened to the solenoid socket.
5. Due to heating solenoid coils, directional spool valves should be put as to eliminate the possibility of incidental touch while using, or, they should be equipped with the coil covers (in accordance with the European standards PN-EN ISO 13732-1 and PN-EN 982).

## SCHEMES

Graphic symbols for 3- position directional spool valves




Graphic symbols for 2- position directional spool valves




Graphic symbols for spools


working and indirect positions




working positions




working and indirect positions






working positions





working and indirect positions





working positions





E





EA





EB





F





FA





FB





G




GA





GB





H





HA





HB




J




JA




JB





L





LA




LB




M




MA





MB





P





PA




PB





Q




QA





QB




R





RA





RB




T




TA




TB




U





UA





UB





V



VA




VB



W



WA



WB

### NOTES:





Spool **E** has the version **E1** with indirect positions like for spool **P**.

Spool **W** allows to open the flow in central position in 3% of nominal flow

Spool **Q** allows to open the flow in central position in 6% of nominal flow


## SCHEMES

### Graphic symbols for 2- position directional spool valves




### Graphic symbols for spools


working and indirect positions




working positions




working and indirect positions




working positions



## OVERALL AND CONNECTION DIMENSIONS



electrical connection type		dimension H
plug-in-connectors ISO 4400 type	control voltage - DC 12V, 24V, 110V	86
plug-in-connectors ISO 4400 type with rectifier	control voltage - AC 110V, 230V	93




- 1 - Solenoid **a**
- 2 - Solenoid **b**
- 3 - Plug-in-connector **A** (ISO 4400 type)
- 4 - Plug-in-connector **B** (ISO 4400 type)
- 5 - Plug-in-connector (ISO 4400 type) with rectifier
- 6 - **O-ring 9,2 x 1,8** - 4 pcs/kit
- 7 - Directional spool valve size with **2 solenoids - a, b**
  - **3-position directional spool valve springs centered**  
(spool schemes: E, F, G, H, J, L, M, Q, R, T, U, V, W - according to page 3)
  - **2-position directional spool valve without return springs**
  - **2-position directional spool valve without springs and with detent**  
(spool schemes: A, C, D - according to page 4)
- 8 - Directional spool valve size with **1 solenoid - a**
  - **2-position springs centered**  
(spool schemes: A, C, D, EA, FA, GA, HA, JA, LA, MA, PA, QA, RA, TA, UA, VA, WA - according to page 3 and 4)
- 9 - Directional spool valve size with **1 solenoid - b**
  - **2-position springs centered**  
(spool schemes: B, Y, EB, FB, GB, HB, JB, LB, MB, PB, QB, RB, TB, UB, VB, WB - according to page 3 and 4)
- 10 - Porting pattern for directional spool valve  
configuration of connection holes in accordance with the following standards:
  - **CETOP RP 121H** - identified by CETOP 4.2-4-03-320 (nominal size **CETOP 03**)
  - **ISO 4401** - identified by ISO 4401-03-02-0-94 mounting bolts **M5 x 50 - 10.9** in accordance with **PN -EN ISO 4762** - 4 pcs/kit, tightening torque **Md = 9Nm**
- 11 - Subplate surface required

## PERFORMANCE CURVES

measured at viscosity  $\nu = 41 \text{ mm}^2/\text{s}$  and temperature  $t = 50^\circ\text{C}$

### Flow resistance curves

Characteristic curves  $\Delta p(Q)$  for directional spool valves type WE6...-12/... for various spool types




Spool type schemes according to page 3, 4	Performance diagram number			
	flow direction			
	P → A	P → B	A → T	B → T
A, B	3	3	-	-
C	1	1	3	1
D, Y	5	5	3	3
E	3	3	1	1
F	2	3	3	5
G	5	3	6	6
H	2	4	2	2
J	1	1	2	1
L, W	1	1	2	2
M	2	4	3	3
P	2	3	3	5
Q	1	1	2	1
R	5	5	4	-
T	5	3	6	6
U	3	1	3	3
V	1	2	1	1

Spool type	Performance diagram number					
G - in central position (P → T scheme- page 3)	flow direction					
	P → A	P → B	P → T	A → T	B → T	B → A
	-	-	7	-	-	-
R - in shifted position (B → A, scheme- page 3)	flow direction					
	P → A	P → B	P → T	A → T	B → T	B → A
	-	-	-	-	-	8

### Flow limits curves

Characteristic curves  $p-Q$  for directional spool valves type WE6...-12/... with DC solenoids for various spool types



#### NOTES:

Above flow limits are related to symmetrical flow through all ports i.e. if the oil flows from port **P** to port **A**, then the same flow rate is from port **B** to

port **T** (applied to directional control valves with 4 service ports). Degree of asymmetry affects adversely the parameters.

Spool type schemes according to page 3, 4	Performance diagram number
E, L, U	1
H, J, M, W, C/OF, D/OF	2
C/O, D/O	3
F, P	4
A, B	5
V	6
A/O	7
R	8
T	9
C, D	10
Q	11
G	12

## HOW TO ORDER

	<b>WE</b>	<b>6</b>		<b>/</b>							<b>★</b>
--	-----------	----------	--	----------	--	--	--	--	--	--	----------

### Number of service ports

**3 - for spools A, B** = **3**

**4 - for the other spools** = **4**

### Nominal size (NS)

**NS6** = **6**

### Spool type

**spool schemes** - on page 3, 4

### Series number

(10-19) - connection and installation dimensions unchanged = 1X

**series 12** = **12**

### Spool positioning

**spring centering** = **no designation**

without springs return = 0

without springs return with detent = OF

### Control voltage for solenoids

DC voltage 12V DC = G12

**DC voltage 24V DC** = **G24**

DC voltage 110V DC = G110

AC voltage 110V AC 50Hz (wtyk z prostownikiem) = W110R

**AC voltage 230V AC 50Hz** (wtyk z prostownikiem) = **W230R**

### Manual override

solenoids without manual override = no designation

**solenoids with manual override** = **N**

### Electrical connection

**plug-in-connector without LED** = **Z4**

plug-in-connector with LED = Z4L

### Throttle insert (in port P)

**without throttle insert** = **no designation**

throttle insert  $\phi$  0,8 = B 08

throttle insert  $\phi$  1,0 = B 10

throttle insert  $\phi$  1,2 = B 12

### Sealing

**NBR** (for fluids on mineral oil base) = **no designation**

FPM (for fluids on phosphate ester base) = V

Further requirements in clear text (to be agreed with the manufacturer)


### NOTES:

Directional spool valve should be ordered according to the above coding.

The symbols in bold are preferred versions in short delivery time.

Coding example: 4WE6 E – 12/G24 N Z4 B08

## EXAMPLE OF APPLICATION IN HYDRAULIC SYSTEM



## SUBPLATES AND MOUNTING BOLTS

Subplates must be ordered according to the data sheet  
**WK 496 480**. Subplates:

- G 341/01 - threaded connection G 1/4
- G 342/01 - threaded connection G 3/8
- G 341/02 - threaded connection M14 x1,5
- G 342/02 - threaded connection M16 x1,5

Subplates and bolts fixing directional valve **M5 x 50 - 10,9**  
in accordance with PN -EN ISO 4762 - 4 pcs/kit)  
must be ordered separately.



# Directional spool valve type WE6.../SO 472 electrically operated special version

## APPLICATION, DESCRIPTION OF OPERATION

like in standard, according to **page 1**

## TECHNICAL DATA

Hydraulic fluid	mineral oil				
Required filtration	up to 16 μm				
Recommended filtration	up to 10 μm				
Nominal fluid viscosity	37 mm <sup>2</sup> /s at temperature 55 °C				
Viscosity range	2,8 up to 380 mm <sup>2</sup> /s				
Fluid temperature range (in a tank)	recommended	40 °C do 55 °C			
	max	-20 °C do +70 °C			
Ambient temperature range	- 20 °C do +50 °C				
Maximum operating pressure	ports P, A, B	31, 5 MPa			
	port T	21 MPa			
Flow section in central position schemes on page 3	spool	Q	W		
	flow section	6 % nominal flow	3 % nominal flow		
Switching time	ON	up to 60 ms			
	OFF	up to 40 ms			
Maximum switching frequency	15000 on/h				
Weight	with 1 solenoid	max 1,5 kg			
	with 2 solenoids	max 2,1 kg			
Supply voltage for solenoids	DC			AC (plug-in connector with rectifier)	
	12V	24V	110V	230V - 50Hz	110V - 50Hz
Supply voltage tolerances	±10%				
Power requirement (DC)	30 W				
Insulation	IP 67				
Solenoid coil temperature	max 150 °C				



## ASSEMBLY AND APPLICATION REQUIREMENTS

1. Only valve working properly and suitably installed may be connected to an electric system. Only skilled workers are allowed to connect and disconnect electric system.
2. Due to heating solenoid coils, directional spool valves should be put as to eliminate the possibility of incidental touch while using, or, they should be equipped with the coil covers (in accordance with the European standards PN-EN ISO 13732-1 and PN-EN 982).

## SCHEMES, PERFORMANCE CURVES

like in standard, according to **pages: 3, 4, 6**

## OVERALL AND CONNECTION DIMENSIONS



- 1 - Solenoid **a**
- 2 - Solenoid **b**
- 3 - Electric feeder cable **3 x 0,5 mm<sup>2</sup>**
- 4 - **O-ring 9,2 x 1,8** - 4 pcs /kit
- 5 - Directional spool valve size with **2 solenoids - a, b**
  - **3-position directional spool valve springs centered** (spool schemes: E, F, G, H, J, L, M, Q, R, T, U, V, W according to page 3)
  - **2-position directional spool valve without return springs**
  - **2-position directional spool valve without springs and with detent** (spool schemes: A, C, D - according to page 4)
- 6 - Directional spool valve size with **1 solenoid - a**
  - **2-position springs centered** (spool schemes: A, C, D, EA, FA, GA, HA, JA, LA, MA, PA, QA, RA, TA, UA, VA, WA - according to page 3 and 4)
- 7 - Directional spool valve size with **1 solenoid - b**
  - **2-position springs centered** (spool schemes: B, Y, EB, FB, GB, HB, JB, LB, MB, PB, QB, RB, TB, UB, VB, WB - according to page 3 and 4)
- 8 - Porting pattern for directional spool valve configuration of connection holes in accordance with the following standards:
  - **CETOP RP 121H** - identified by **CETOP 4.2-4-03-320** (nominal size **CETOP 03**)
  - **ISO 4401** - identified by **ISO 4401-03-02-0-94**
- 9 - Subplate surface required

## HOW TO ORDER

<b>4</b>	<b>WE</b>	<b>6</b>	<b>—</b>	<b>/</b>		<b>N</b>	<b>Z4</b>	<b>/</b>	<b>/</b>	<b>SO 472</b>
----------	-----------	----------	----------	----------	--	----------	-----------	----------	----------	---------------

### Number of service ports

4 service ports = 4

### Nominal size (NS)

NS6 = 6

### Spool type

spool schemes - on page 3, 4 (without spools A, B)

### Series number

(10-19) - connection and installation dimensions unchanged = 1X  
series 12 = 12

### Spool positioning

spring centering = no designation  
without springs return = 0  
without springs return with detent = OF

### Control voltage for solenoids

DC voltage 12V DC = G12  
DC voltage 24V DC = G24  
DC voltage 110V DC = G110

### Manual override

solenoids with manual override = N

### Electrical connection

electric cable 3 x 0,5 mm<sup>2</sup>; 3m length = Z4

### Throttle insert (in port P)

without throttle insert = no designation  
throttle insert  $\phi$  0,8 = B 08  
throttle insert  $\phi$  1,0 = B 10  
throttle insert  $\phi$  1,2 = B 12

### Sealing

**NBR** (for fluids on mineral oil base) = no designation  
FPM (for fluids on phosphate ester base) = V

### Special version

DC solenoids equipped with electric feeder cable of 3m length, **insulation IP67** = **SO 472**

### NOTES:

Directional spool valve should be ordered according to the above coding.  
Coding example: 4WE6 J – 12/G24 N Z4 / B08 /SO 472

## **SUBPLATES AND MOUNTING BOLTS**

like in standard, according to **page 8**

PONAR Wadowice S.A.  
ul. Wojska Polskiego 29  
34-100 Wadowice  
tel. +48 33 488 29 00  
fax. +48 33 488 21 03  
[www.ponar-wadowice.pl](http://www.ponar-wadowice.pl)

